	Amp + Effects Processors									Effects-Only Processors			
	Helix Floor	Helix Rack/Control	Helix LT	HX Stomp XL	HX Stomp	POD Go Wireless	POD Go	POD HD Pro X/FBV 3	Pocket POD	HX Effects	М9	M5	DL4
Amp Models	86		86		83		30 (HD)	32 (Classic)					
Effect Models	226		226		206		104 "M-Class"	15 (Classic)	226	103 "M-Class" 15 "M-Class"		15 "M-Class"	
Presets	1,024 (8 setlists x 32 banks x 4 presets)		128 (32 banks x 4 presets) 126 (42 banks x 3 presets)		256 (2 setlists x 32 banks x 4 presets)		512 (8 setlists x 16 banks x 4 presets)	300+	128 (32 banks x 4 presets)	24 scenes	24	3	
Simultanious Processing Blocks	Up to 32 (DSP permitting)			Up to 8 (DSP permitting)		Up to 10 (semi-fixed, DSP permitting)		Up to 10 (DSP permitting) + Looper	3 (Amp/Cab, effects, gate)	Up to 9 (DSP permitting)	3 + Looper	1	1 + Looper
Signal Flow Options	Up to 4 stereo, serial or parallel			Up to 2 stereo, serial or parallel		Serial		Up to 2 stereo, serial or parallel	Serial	Up to 2 stereo, serial or parallel	Serial		
Snapshots	8 per preset			4 per preset 3 per preset		4 per preset			-	4 per preset	4 per preset		
Impulse Responses (IRs)	128x 1024 or 2048-point			128x 1024 or 2048-point		128x 1024 point			-	128x 1024 or 2048-point			
Global EQ Bands	3 fully parametric + variable low & high cut			3 fully parametric + variable low & high cut		3 fully parametric + variable low & high cut		3 fully parametric + variable low & high cut	-				
Main Display (in/cm)	6.2/16.5 (Color)			2.4/6 (Color)		4.3/11 (Color)		2.8/7 (Monochrome)	1.6/4 (Monochrome)		2.3/6 (color backlight)		
Footswitches	12 capacitive touch w/ RGB rings + EXP toe switch	12 capacitive touch w/ RGB rings	12 capacitive touch w/ RGB rings + EXP toe switch	8 capacitive touch w/ RGB rings + 2x external	3 capacitive touch w/ RGB rings + 2x external	8 with RGB rings + EXP toe switch + 2x external		13 + EXP toe switch		8 capacitive touch with RGB rings	7 with RGB LEDs	2	4
Footswitch Modes	Stomp, Preset, Snapshot, Looper, Pedal Edit			Stomp, Preset, Snapshot, Looper, Pedal Edit	Stomp, Preset, Snapshot	Stomp, Preset, Sr	Stomp, Preset, Snapshot, Looper			Stomp, Preset, Snapshot, Looper, Pedal Edit	Stomp, Looper	Stomp	Preset/Stomp, Looper
Footswitch Types	Latching, Momentary			Latching, Momentary		Latching		Latching		Latching, Momentary	Latching, Momentary Latching		-
Looper Types	6 Switch, 1 Switch, Shuffling			6 Switch, 1 Switch, Shuffling 1 Switch, Shuffling		6 Switch, 1 Switch, Shuffling		7 Switch		6 Switch, 1 Switch, Shuffling	6 Switch		4 Switch
Looper Memory (Full Speed)	60 sec mona/30 sec stereo			60 sec mono/30 sec stereo		40 sec mono/20 sec stereo		24 sec mono	-	60 sec mono/30 sec stereo	28 sec mono		14 sec mono
Looper Memory (1/2 Speed)	120 sec mono/60 sec stereo			120 sec mono/60 sec stereo		80 sec mono/40 sec stereo		48 sec mono		120 sec mono/60 sec stereo	56 sec mono		28 sec mono
1/4" Inputs	Guitar, Aux, Return 1-4 Guitar, Return 1-2		Stereo L/R, Return L/R		Guitar, Stereo Return		Guitar, Line L/R, Return L/R	Guitar In	Stereo L/R, Return L/R	Stereo L/R			
1/4" Outputs	Main L/R, Send 1-4 Main L/R, Send 1-2		Main L/R, Send 1-2	Main L/R, Stereo Send		Main L/R, Amp Out, Stereo Send		Main L/R, Dry Thru, Send L/R	Amp Out	Main L/R, Send 1-2 Stereo L/R			
XLR Inputs	Mic pre w/ phantom power		***		***		Mic pre w/ phantom power	-					
XLR Outputs	Main L/R			***		694		Main L/R					
Effect Loop(s)	4x Send, 4x Return, stereo-linkable 2x Send, 2x Ret		2x Send, 2x Return, stereo-linkable	2x Send, 2x Return, stereo-linkable		1x mono/stereo Send, 1x mono/stereo Return		L/R stereo Send, L/R stereo Return		2x Send, 2x Return, stereo-linkable			
Digital In	Variax VDI, S/PDIF Variax VDI, S/PDIF, AES/EBU w/ BNC wordclock Variax VDI						Variax VDI, S/PDIF, AES/EBU						
Digital Out	S/PDIF, AES/EBU/L6 LINK					***		S/PDIF, AES/EBU/L6 LINK		***			
Headphones	1/4* stereo			1/4" stereo		1/4" stereo		1/4" stereo	3.5mm Stereo				
MIDI	In, Out/Thru + USB			In, Out/Thru + USB		USB		In, Out/Thru		In, Out/Thru + USB	In, Out/Thru + USB In, Out/Thru		
USB Audio Interface	8-In, 8-Out With Re-Amping			8-in, 6-out w/ re-amping		4-in, 4-out w/ re-amping		2-in, 2-out		-			
Master Remote Control	Command Center			Command Center				Yes		Command Center			
Variable Impedance Circuitry	Guitar In			Stereo L/R In				Guitar In					
Chassis	Extruded aluminum w/ cast aluminum side panels	Rack: cast aluminum and bent steel; Control: bent steel w/ ABS side panels	Bent steel w/ ABS side panels	Cast al	uminum	Bent steel and p	olycarbonate	Cast aluminum and bent steel	Plastic	Bent steel w/ ABS side panels	Bent steel Cast aluminum		
Treadle	Cast aluminum		Bent steel		-	Cast aluminum		Bent steel					
Scribble Strip LCDs	13 x 27/5cm	12 x 2"/5cm								6 x 2"/5cm	***		
1/4" Exp Pedal Inputs	EXP 2, EXP 3	EXP 1, EXP 2, EXP 3, EXP Toe Switch	EXP 2 (shared w/ Amp Control Out 1/2)	EXP 1/2 (TRS; shared w/ Footswitch 7/8)	EXP 1/2 (TRS; shared w/ Footswitch 4/5)	EXP 2 (shared with	Footswitch 7/8)	Expression Pedal		EXP 1, EXP 2 (shared w/ Amp Control 1/2)	EXP 1, EXP 2	Expres	ssion Pedal
External Amp Control Outputs	2 (1-	=Tip, 2=Ring)	2 (1=Tip, 2=Ring; Shared with EXP 2; Globally Selectable)			***				4 (shared w/ EXP 1, EXP 2)			
G10T Wireless Transmitter				G10TII Included		***	***	-					
Relay Wireless Receiver	*** ****			DC-3		Internal (125'/40m Line-of-sight)	-		-				
Power		IEC				DC 3.54		IEC	DC-1g / (4) AAA batteries	DC-3	PX-2g	DC-1g	DC-DL4 / PX-2g / (4) C batteries
Product Height (in/cm)	3.61/92	5.25/133	3.61/92	2.7/68	2.6/66			3.5/88	2/5	2.81/71	2.4/6	2.4/6	2.5/6
Product Width (in/cm)	22.05/560	19/483	20.86/530	12.4/316	7.01/178	9.1/2		19/483	5/13	10.8/274	10.5/27	6/15	10/25
Product Depth (in/cm)	11.87/301	9.5/241	11.87/301	4.7/120	4.96/126	14.1/		7.5/19	3.5/9	7.84/199	6.5/17	6.5/17	6/15
Product Weight (lb/kg)	14.6/6.6	9.3/4.2	12/5.4	3.3/1.5	1.75/0.79	5.2/ 2.35	5.5/2.5	8.65/3.92	.4/.67	4.9/2.22	3/1.36	2.5/1.13	3.1/1.40